



Google earth

feet 100
meters 30



— Fence
● walk-gate
++ drive thru-gate

~225'

4' * 6'



PRESCOTT FENCE COMPANY
6576 INTERCAL WAY
PRESCOTT, ARIZONA 86301
(928) 445-4211 FAX: (928) 445-7011

CHAINLINK FENCE SPECIFICATION

FABRIC: 48" 11 GA. GBW (2" Mesh) KK CHAIN-LINK FABRIC.

TOP RAIL: 1 5/8" O.D. SWEDGE END .065 TUBING, 1.10 lbs. per foot. Top rail 21' in length.

LINE POST: 2" O.D. .065 TUBING, 1.29 lbs. per foot. Line posts set 10' on center maximum spacing. Concrete footing: 8" diameter, 18" depth.

TERMINAL POST: 2 1/2" O.D. .065 TUBING POST, 1.60 lbs. per foot. Concrete footing: 8" diameter, 24" depth.

GATES: SINGLE SWING GATE: Framework of 1 5/8" .065 TUBING, 1.10 lbs. per foot.
REMOVABLE GATE PANEL: Framework of 1 5/8" .065 TUBING, 1.10 lbs. per foot.
DOUBLE SWING GATE: Framework of 1 5/8" .065 TUBING, 1.10 lbs. per foot.
Gates braced and trussed as necessary. Same fabric as fence.

GATE POST: SINGLE SWING GATE: 2 1/2" O.D. .065 TUBING POST, 1.60 lbs. per foot. Concrete footing: 8" diameter, 24" depth.
REMOVABLE GATE PANEL: 2 1/2" O.D. .065 TUBING POST, 1.60 lbs. per foot. Concrete footing: 8" diameter, 24" depth.
SINGLE SWING GATE: 2 1/2" O.D. LG-40 PIPE POST, 3.12 lbs. per foot. Concrete footing: 8" diameter, 24" depth.
DOUBLE SWING GATE: 4" O.D. LG-40 PIPE, 6.56 lbs. per foot. Concrete footing: 12" diameter, 36" depth.

TENSION WIRE: 9 GA. SMOOTH GALVANIZED TENSION WIRE attached to bottom of fence fabric with 12 GA. STEEL HOG RING spaced 24" on center.

FITTINGS: REGULAR BRACE BAND & CARRIAGE BOLT, PRESSED STEEL RAIL END, PRESSED STEEL LOOP CAP, PRESSED STEEL DOME CAP, 3/16" X 5/8" STEEL TENSION BAR, REGULAR TENSION BAND & CARRIAGE BOLT.

TIE WIRE: 8 1/4" STEEL 11 GA. TIE WIRE spaced 15" on center for line posts & 24" on center for rails.

POST FOOTING: HAND MIX - POST MIX CONCRETE.



PRESCOTT FENCE COMPANY
6576 INTERCAL WAY
PRESCOTT, ARIZONA 86301
(928) 445-4211 FAX: (928) 445-7011

CHAINLINK FENCE SPECIFICATION

FABRIC: 72" 11 GA. GBW (2" Mesh) KK CHAIN-LINK FABRIC.

TOP RAIL: 1 5/8" O.D. SWEDGE END .065 TUBING, 1.10 lbs. per foot. Top rail 21' in length.

LINE POST: 2" O.D. .065 TUBING POST, 1.29 lbs. per foot. Line posts set 10' on center maximum spacing. Concrete footing: 8" diameter, 18" depth.

TERMINAL POST: 2 1/2" O.D. .065 TUBING POST, 1.60 lbs. per foot. Concrete footing: 8" diameter, 24" depth.

GATES:
SINGLE SWING GATE: Framework of 1 5/8" .065 TUBING, 1.10 lbs. per foot.
REMOVABLE GATE PANEL: Framework of 1 5/8" .065 TUBING, 1.10 lbs. per foot.
DOUBLE SWING GATE: Framework of 1 5/8" .065 TUBING, 1.10 lbs. per foot.
Gates braced and trussed as necessary. Same fabric as fence.

GATE POST:
SINGLE SWING GATE: 2 1/2" O.D. .065 TUBING POST, 1.60 lbs. per foot. Concrete footing: 8" diameter, 24" depth.
REMOVABLE GATE PANEL: 2 1/2" O.D. .065 TUBING POST, 1.60 lbs. per foot. Concrete footing: 8" diameter, 24" depth.
SINGLE SWING GATE: 2 1/2" O.D. LG-40 PIPE POST, 3.12 lbs. per foot. Concrete footing: 8" diameter, 24" depth.
DOUBLE SWING GATE: 4" O.D. LG-40 PIPE POST, 6.56 lbs. per foot. Concrete footing: 12" diameter, 36" depth.

TENSION WIRE: 9 GA. SMOOTH GALVANIZED TENSION WIRE attached to bottom of fence fabric with 12 GA. STEEL HOG RING spaced 24" on center.

FITTINGS: REGULAR BRACE BAND & CARRIAGE BOLT, PRESSED STEEL RAIL END, PRESSED STEEL LOOP CAP, PRESSED STEEL DOME CAP, 3/16" X 5/8" STEEL TENSION BAR, REGULAR TENSION BAND & CARRIAGE BOLT.

TIE WIRE: 8 1/4" STEEL 11 GA. TIE WIRE spaced 15" on center for line posts & 24" on center for rails.

POST FOOTING: HAND MIX - POST MIX CONCRETE.